



Available only from the technology experts at SMART PARK

- **9 Optional Guidelines**
- **Very Good Low Light Capability**
- **Extremely compact design.**
- **Built in microphone.**
- **Multiple, Adjustable mounting systems**
- **High Resolution Digital Imager**
- **160 Degree High Quality Lens**
- **Fits any vehicle**
- **100% Waterproof (IP68 Tested)**
- **Mirror/Normal Switch**

Item	CAM326
Dimension (mm)	Φ30 x 30(H)
Image Sensor	1/4" OV7960 Analog
Lens	Focal Length 1.9mm Maximum Aperture F2.0
View angle (Horizontal)	100°
View angle (Vertical)	80°
IR LED	No
Microphone	No
Power Requirements	DC 12V/24V
Power consumption	Max. 30mA
Mirror control	Yes
Video format	NTSC
Video signal output	1 Vp-p (75ohm)
Effective Pixel Resolution	NTSC 656 x492
S/N (dB)	Better than 48dB
Illumination (min.)	0.1 Lux
Additional Specifications	Automatic Exposure/Gain Control
Self diagnostic controller	Auto White Balance
	Aperture & Gamma Correction
Waterproof and dustproof	IP68
Operating Temperature Range	-30°C ~ +85 °C RH95% Max
Storage temperature	-40°C~+105°C RH95% Max
Weight	42g
Guide Line	NO