



Adjustable Speaker w/ Tri-color LED



Learning Capability



16 Program Options
incl. Front Active Learning Technology



Auto-Mute Function



Low Profile Paintable
Push In (PI) Sensors



Front or Rear Install
Adjustable Range 3ft-7ft

- The most advanced sensor system available.
- 2 or 4 Sensor / Front or Rear - one kit for all
- Automatic active learning front system - Active when you need it & silent when you don't.
- Adjustable range and sensitivity
- Installs into plastic or metal bumpers.
- Learning capability to ignore vehicle mounted objects
- Auto-mute function for use when towing
- Adjustable Audio/Visual display unit included with high quality speaker.
- Advanced Visual Display Available
- Low profile, small diameter sensors
- Self-diagnostic check on startup



OE Style Recessed Sensor Option

Item		PDC125PI
Power Requirements		DC 12V
Current Draw		<120mA
The Number of Sensors		4 pcs
Detecting Distance		0~200 cm
Sensor Cable Length		6 m
Operating Temperature Range		-30°C ~ +80°C
Storage Temperature		-40°C ~ +100°C
Ultrasonic Frequency		58 KHz
Alarm Type		Speaker
Supporter		Yes
Mode		Rear/Front
Setting Function		Rear/Front, 2/4 Sensor, Far/Near Range, High/Low Sensitivity
Zone Range	Center	0~40~100~200 cm
	Side Sensor	0~40~80 cm
Response time		0.2S